



ELSEVIER

Contents lists available at ScienceDirect

Data in Brief

journal homepage: www.elsevier.com/locate/dib

Data Article

Data on fluoride concentration in drinking water resources in Iran: A case study of Fars province; Larestan region

Mohammad Hadi Dehghani^{a,b,*}, Gholam Ali Haghghat^a,
Mahmood Yousefi^a

^a Department of Environmental Health Engineering, School of Public Health, Tehran University of Medical Sciences, Tehran, Iran

^b Institute for Environmental research, Center for Solid Waste Research, Tehran University of Medical Sciences, Tehran, Iran

ARTICLE INFO

Article history:

Received 3 May 2018

Received in revised form

16 May 2018

Accepted 18 May 2018

Available online 24 May 2018

Keywords:

Fluoride

Drinking water

Fars province

Larestan

Iran

ABSTRACT

Fluoride is a natural element among minerals, geochemical sediments and natural water systems which is entered to body chain by drinking water. Groundwater is the main and the best source of drinking water in southern areas of Iran especially in the cities of Lar and Gerash (Fars province). So due to the health significance fluoride including dental and skeletal fluorosis, fertility, abortion and thyroid diseases, etc., measuring has high importance in the water resources of this region of Iran. Fluoride concentration was 0.35–3.46 mg/L and 78.26% drinking water sources contains fluoride concentration above the WHO guideline.

© 2018 The Authors. Published by Elsevier Inc. This is an open access article under the CC BY license

(<http://creativecommons.org/licenses/by/4.0/>).

Specifications Table

Subject area	Water chemistry
More specific subject area	Water fluoride
Type of data	Tables, Figure

* Corresponding author at: Department of Environmental Health Engineering, School of Public Health, Tehran University of Medical Sciences, Tehran, Iran.

E-mail address: hdehghani@tums.ac.ir (M.H. Dehghani).

<https://doi.org/10.1016/j.dib.2018.05.112>

2352-3409/© 2018 The Authors. Published by Elsevier Inc. This is an open access article under the CC BY license (<http://creativecommons.org/licenses/by/4.0/>).

How data was acquired	Samples were examined in Water and Wastewater Laboratory of the Health Center of Shiraz Valfajr Shohadaye and had been assessed by sodium 2-(parasulfophenylazo)-1, 8-dihydroxy-3, 6-naphthalene disulfonate (SPADNS) colorimetric method based on Standard Methods. SPADNS standard methods with a spectrophotometer DR model 5000 of HACH Company
Data format	Raw, Analyzed
Experimental factors	Fluoride concentration above, in abstract section, were analyzed according to the standards for water and wastewater treatment handbook.
Experimental features	Determine the concentration levels of fluoride
Data source location	Larestan, Fars province, Iran
Data accessibility	The data are available whit this article

Value of the data

- Knowledge of fluoride level in potable groundwater is important for health care personnel and policymakers.
- Long-term consumption of drinking water with a high fluoride concentration leads to many adverse effects on human including dental and skeletal fluorosis [1–4].
- Based on the data article, DE fluoridation of drinking water resource could be recommended in this region with high fluoride concentrations.

1. Data

Fluoride concentration (mg/L) in drinking water of Larestan region, fluoride concentration in drinking water according to Institute of Standards and Industrial Research of Iran are summarized in Tables 1 and 2 respectively.

2. Experimental design, materials and methods

2.1. Study area description

Lar and Gerash are located between 27° and 60 min to 28° and 25 min' north latitude and 52° and 25 min to 55° and 38 min east of Greenwich meridian: the two cities were called Larestan city before, and are located in the southern province of Fars and were separated in 2011 during administrative divisions. It leads to Jahrom from north, to Darab and Zarin dasht from north-east, to Firouzabad from north-west, Chirokarzine, Khange, and to the province of Hormozgan from south, west to the city of Lamerd and Mehr and east to the Finn of Bandar Abbas. The city with an average altitude of 900 m above sea level, is one of the hot and dry regions of Iran that is allocated 1.6 (17%) of Fars Province. Larestan has of hot and dry climate with mild winters and hot and very dry summers. Larestan rainfall was 198.8 mm during the 20-year statistics of Larestan airport weather station. The highest annual precipitation is related to January and February that precipitations were long but had low intensity. In July and August rainfalls were at minimum level with short time of raining and high intensity (Fig. 1).

2.2. Sample collection and analytical procedures

92 wells have been selected as randomly and were sampled regularly Four times a year from 2010 to 2011. Samples were examined in Water and Wastewater Laboratory of the Health Center of Shiraz

Table 1
Fluoride concentration (mg/L) in drinking water of Larestan region, Fars province, Iran.

Number ^a	Fluoride concentration (mg/L)	Number ^a	Fluoride concentration (mg/L)	Number ^a	Fluoride concentration (mg/L)
1	2.38	32	0.67	63	1.07
2	1.92	33	0.62	64	1.3
3	2.64	34	0.35	65	1.41
4	2.42	35	0.63	66	0.91
5	2.14	36	0.64	67	0.76
6	1.54	37	0.65	68	1.14
7	1.56	38	1.65	69	1.28
8	2.66	39	0.8	70	1.96
9	2.84	40	0.92	71	2.35
10	2.66	41	0.85	72	2.29
11	2.86	42	1.33	73	1.83
12	3.46	43	0.45	74	2.02
13	3.44	44	1.48	75	1.63
14	2.36	45	1.53	76	1.08
15	3.28	46	1.13	77	1.72
16	2.08	47	1.1	78	2.48
17	2.28	48	1.28	79	2.73
18	2.95	49	1.39	80	1.84
19	2.8	50	1.7	81	1.65
20	2.3	51	1.9	82	2.1
21	2.58	52	1.59	83	1.95
22	1.62	53	0.77	84	2.1
23	2	54	0.51	85	2.88
24	2.4	55	0.86	86	1.23
25	0.8	56	1.65	87	1.52
26	0.64	57	0.83	88	1.44
27	0.96	58	0.85	89	1.67
28	0.64	59	2.02	90	1.46
29	0.96	60	1.71	91	1.43
30	2.02	61	1.43	92	2.73
31	0.71	62	1.7		
WHO guideline	0.5–1.5				

^a Number of supply sources for drinking water.

Table 2
Fluoride concentration in drinking water, according to Institute of Standards and Industrial Research of Iran [5–10].

The annual average maximum daily air temperatures (°C)	The maximum allowable amount of fluoride (mg/l)	Desirable level (mg/l)	The minimum allowable amount of fluoride (mg/l)
10–12	2.4	1.2	1.1
12–14.6	2.2	1.1	1
14.6–17.7	2	1	0.9
17.7–21.5	1.8	0.9	0.8
21.5–26.3	1.6	0.8	0.7
26.3–32.5 [*]	1.4 [*]	0.7 [*]	0.6 [*]

^{*} These target values accounts for Larestan region since the annual average maximum daily temperature is about 32.5 °C there.

Valfajr Shohadaye and had been assessed by sodium 2-(parasulfophenylazo)-1, 8-dihydroxy-3, 6-naphthalene disulfonate (SPADNS) colorimetric method based on Standard Methods. SPADNS standard methods with a spectrophotometer DR model 5000 of HACH Company [11–16]. Analytical method for fluoride determination between the 0.0625–1.75 mg L⁻¹ ($r=0.9993$) and the higher level of this range were diluted and measured. The fluoride concentration was assessed by Spectrophotometer (DR/5000, USA) and obtained limits of determination (LOD) and quantification (LOQ)



Fig. 1. Location of the study area in Larestan city, Fars province, Iran.

were 0.12 ppm and 0.37 ppm respectively [1,17–24]. This method is acceptable for USEPA and can be reported after the needed analyzes [1,25,26]. We used two 10 mm cubic cell in this method, one for the deionized water and the other for the sample. Then we added 2 mL SPADNS solution to each cell and keep stirring for a minute. Finally, we read each cell with the spectrophotometer.

Acknowledgements

The authors want to thank authorities of Tehran University of Medical Sciences (Grant 90-01-27-12764) for their comprehensives support for this study.

Transparency document. Supporting information

Transparency data associated with this article can be found in the online version at <http://dx.doi.org/10.1016/j.dib.2018.05.112>.

References

- [1] M. Yousefi, M. Ghoochani, A.H. Mahvi, Health risk assessment to fluoride in drinking water of rural residents living in the Poldasht city, Northwest of Iran, *Ecotoxicol. Environ. Saf.* 148 (2018) 426–430.
- [2] V. Kazemi Moghadam, M. Yousefi, A. Khosravi, M. Yaseri, A.H. Mahvi, M. Hadei, A.A. Mohammadi, Z. Robati, A. Mokamel, High concentration of fluoride can be increased risk of abortion, *Biol. Trace Elem. Res.* 182 (2018) 1–4.

- [3] A.A. Mohammadi, M. Yousefi, M. Yaseri, M. Jalilzadeh, A.H. Mahvi, Skeletal fluorosis in relation to drinking water in rural areas of West Azerbaijan, Iran, *Sci. Rep.* 7 (2017) 1–7.
- [4] A.A. Mohammadi, K. Yaghmaeian, H. Faraji, R. Nabizadeh, M.H. Dehghani, J.K. Khaili, et al., Temporal and spatial variation of chemical parameter concentration in drinking water resources of Bandar-e Gaz City using geographic information system, *Desalination Water Treat.* 68 (2017) 170–176.
- [5] F.B. Asghari, J. Jaafari, M. Yousefi, A.A. Mohammadi, R. Dehghanzadeh, Evaluation of water corrosion, scaling extent and heterotrophic plate count bacteria in asbestos and polyethylene pipes in drinking water distribution system, *Human. Ecol. Risk Assess.: Int. J.* 24 (2018) 1138–1149.
- [6] F.B. Asghari, A.A. Mohammadi, Z. Aboosaedi, M. Yaseri, M. Yousefi, Data on fluoride concentration levels in cold and warm season in rural area of Shout (West Azerbaijan, Iran), *Data Brief* 15 (2017) 528–531.
- [7] M.H. Dehghani, M. Faraji, A. Mohammadi, H. Kamani, Optimization of fluoride adsorption onto natural and modified pumice using response surface methodology: isotherm, kinetic and thermodynamic studies, *Korean J. Chem. Eng.* 34 (2017) 454–462.
- [8] M. Yousefi, A.A. Mohammadi, M. Yaseri, A.H. Mahvi, Epidemiology of drinking water fluoride and its contribution to fertility, infertility, and abortion: an ecological study in West Azerbaijan Province, Poldasht County, Iran, *Fluoride* 50 (2017) 343–353.
- [9] A. Assadi, M.H. Dehghani, N. Rastkari, S. Nasserri, A.H. Mahvi, Photocatalytic reduction of hexavalent chromium in aqueous solutions with zinc oxide nanoparticles and hydrogen peroxide, *Environ. Prot. Eng.* 38 (2012) 5–16.
- [10] F.B. Asghari, A.A. Mohammadi, M.H. Dehghani, Data on assessment of groundwater quality with application of ArcGIS in Zanjan, Iran, *Data Brief* 18 (2018) 375–379.
- [11] M. Shams, R. Nabizadeh Nodehi, M.H. Dehghani, M. Younesian, A.H. Mahvi, Efficiency of granular ferric hydroxide (GFH) for removal of fluoride from water, *Fluoride* 43 (2010) 61–67.
- [12] M.H. Dehghani MH, G.A. Haghighat, K. Yetilmezsoy, G. McKay, B. Heibati, I. Tyagi, et al., Adsorptive removal of fluoride from aqueous solution using single-and multi-walled carbon nanotubes, *J. Mol. Liq.* 216 (2016) 401–410.
- [13] A. Fadaei, M.H. Dehghani, A.H. Mahvi, S. Nasserri, N. Rastkari, M. Shayeghi, Degradation of organophosphorus pesticides in water during UV/H₂O₂ treatment: role of sulphate and bicarbonate ions, *J. Chem.* 9 (2012) 2015–2022.
- [14] M.H. Dehghani, A.R. Mesdaghinia, S. Nasserri, A.H. Mahvi, K. Azam, Application of SCR technology for degradation of reactive yellow dye in aqueous solution, *Water Qual. Res. J. Can.* 43 (2008) 1–10.
- [15] M.H. Dehghani, M. Ghadermazi, A. Bhatnagar, P. Sadighara, G. Jahed-Khaniki, B. Heibati, et al., Adsorptive removal of endocrine disrupting bisphenol A from aqueous solution using chitosan, *J. Environ. Chem. Eng.* 4 (2016) 2647–2655.
- [16] M. Yousefi, M. Yaseri, R. Nabizadeh, E. Hooshmand, M. Jalilzadeh, A.H. Mahvi, A.A. Mohammadi, Association of hypertension, body mass index and waist circumference with fluoride intake; water drinking in residents of fluoride endemic areas, Iran, *Biol. Trace Elem. Res.* 182 (2018) 1–7.
- [17] H. Soleimani, A. Abbasnia, M. Yousefi, A.A. Mohammadi, F.C. Khorasgani, Data on assessment of groundwater quality for drinking and irrigation in rural area Sarpol-e Zahab city, Kermanshah province, Iran, *Data Brief* 17 (2018) 148–156.
- [18] M. Yousefi, M.H. Dehghani, S.M. Nasab, V. Taghavimanesh, S. Nazmara, A.A. Mohammadi, Data on trend changes of drinking groundwater resources quality: a case study in Abhar, *Data Brief* 17 (2018) 424–430.
- [19] S. Agarwal, I. Tyagi, V.K. Gupta, M.H. Dehghani, J. Jaafari, D. Balarak, et al., Rapid removal of noxious nickel (II) using novel γ -alumina nanoparticles and multiwalled carbon nanotubes: kinetic and isotherm studies, *J. Mol. Liq.* 224 (2016) 618–623.
- [20] M.H. Dehghani, A.M. Fadaei, Photocatalytic oxidation of organophosphorus pesticides using zinc oxide, *Res. J. Chem. Environ.* 16 (2012) 104–109.
- [21] M.H. Dehghani, A.H. Mahvi, N. Rastkari, R. Saeedi, S.H. Nazmara, E. Iravani, Adsorption of bisphenol A (BPA) from aqueous solutions by carbon nanotubes: kinetic and equilibrium studies, *Desalination Water Treat.* 54 (2015) 84–92.
- [22] M.H. Dehghani, A. Najafpoor, K. Azam, Using sonochemical reactor for degradation of LAS from effluent of wastewater treatment plant, *Desalination* 250 (2010) 82–86.
- [23] M.H. Dehghani, A.H. Mahvi, G.R. Jahed, R. Sheikhi, Investigation and evaluation of ultrasound reactor for reduction of fungi from sewage, *J. Zhejiang Univ. Sci. B* 8 (2007) 493–497.
- [24] M.H. Dehghani, M. Farhang, M. Alimohammadi, M. Afsharnia, G. Mckay, Adsorptive removal of fluoride from water by activated carbon derived from CaCl₂-modified *Crocus sativus* leaves: equilibrium adsorption isotherms, optimization, and influence of anions, *Chem. Eng. Commun.* (2018) 1–11.
- [25] M.H. Dehghani, P. Mahdavi, Removal of acid 4092 dye from aqueous solution by zinc oxide nanoparticles and ultraviolet, *Desalination Water Treat.* 54 (2015) 3464–3469.
- [26] M. Ghaderpoori, G.R. Jahed Khaniki, M.H. Dehghani, M. Shams, A. Zarei, Determination of fluoride in bottled water sold in Tehran market, Iran, *Am.-Eurasian J. Agric. Environ. Sci.* 6 (2009) 324–327.